

## 361-230-10(-S2) Spring return actuator

### Description

Spring return actuator for adjusting dampers in HVAC Installations.

- Running time motor 75 s / 90°
- Running time spring 20 s / 90°
- Torque motor 10 Nm
- Torque spring 10 Nm
- Nominal voltage 230 VAC/DC
- Control 2-point
- Auxiliary switch 2x freely adjustable
- Damper size up to approx. 2 m²
- Shaft coupling Clamp  
Ø 9-18 mm / Ø 9-26 mm



### Technical data

#### Electrical data

<b>Nominal voltage</b>	230 VAC/DC, 50/60Hz
<b>Nominal voltage range</b>	85...265 VAC/DC
<b>Power consumption motor (motion)</b>	5.5 W
<b>Power consumption standby (end position)</b>	1.5 W
<b>Wire sizing</b>	11.5 VA
<b>Control</b>	2-point
<b>Connection motor</b>	cable 1000 mm, 2 x 0.75 mm² (halogen free)
<b>Connection feedback potentiometer</b>	-
<b>Connection GUAC</b>	-
<b>Feedback signal</b>	-
<b>361-230-10-S2</b>	
<b>Auxiliary switch</b>	2 x SPDT (ag)
<b>Contact load</b>	5 (2.5) A, 250 VAC
<b>Switching point</b>	0°...95°
<b>Connection auxiliary switch</b>	cable 1000 mm, 6 x 0.75 mm² (halogen free)

### Functional data

<b>Torque</b>	10 Nm
<b>Torque spring</b>	10 Nm
<b>Damper size</b>	up to approx. 2 m <sup>2</sup>
<b>Synchronized speed</b>	±5%
<b>Direction of rotation</b>	selected by mounting
<b>Manual override</b>	manual operation
<b>Angle of rotation</b>	0°...max. 95° can be limited with adjustable mechanical end stops
<b>Running Time motor</b>	75 s / 90°
<b>Running time spring</b>	20 s / 90°
<b>Sound power level motor</b>	< 45 dB(A)
<b>Sound power level spring</b>	< 65 dB(A)
<b>Shaft coupling</b>	clamp ∅ 9-18 mm / ∅ 9-26 mm
<b>Position indication</b>	mechanical with pointer
<b>Service life</b>	> 60 000 cycles (0°...95°...0°)

### Safety

<b>Protection class</b>	II (Double Insulation)
<b>Degree of protection</b>	IP 54
<b>EMC</b>	CE (2014/30/EU)
<b>LVD</b>	CE (2014/35/EU)
<b>RoHS</b>	CE (2011/65/EU - 2015/863/EU - 2017/2102/EU)
<b>Mode of operation</b>	Typ 1 (EN 60730-1)
<b>Rated impulse voltage supply / control</b>	4 kV (EN 60730-1)
<b>Control pollution degree</b>	3 (EN 60730-1)
<b>Ambient temperature normal operation</b>	-30°C...+50°C
<b>Storage temperature</b>	-30°C...+80°C
<b>Ambient humidity</b>	5...95% r.H., non-condensing (EN60730-1)
<b>Maintenance</b>	Maintenance free

### Dimensions/Weight

<b>Dimensions</b>	193 x 96 x 60 mm
<b>Weight</b>	1600 g
<b>Weight (-S2)</b>	1700 g

## Functionality / Properties

### Operating mode

Connect power supply to wire 1+2, actuator drives to position 1 while the pre-tensioned spring is wound up the same time. If the power supply is interrupted, actuator drives back to position 0 by spring power. The actuator is still maintaining the minimum torque at the damper spindle.

The actuator is overload-proof, requires no limit switches and automatically stops when the end stop is reached.

### Direct mounting

Simple direct mounting on the damper shaft with a clamp, protection against rotating with enclosed anti-rotation lock or rather at intended attachment points.


### Manual override

The actuator can only be operated manually while the power supply is off. The supplied lever is used to open and lock the damper position. The lock stays until the power supply is switched on again.

### Signaling

The two integrated auxiliary switches are freely adjustable in the angle of 0 - 95°. There are activated corresponding to the adjusted angle. The damper position can be checked by the mechanical pointer.


## Connector / Security Note



## Safety remarks

- Caution: power supply voltage!
- The device is not allowed to be used outside the specified field of application, especially in airplanes.
- It may only be installed by suitably trained personnel. Any legal regulations or regulations issued by authorities must be observed during assembly.
- The device may only be opened at the manufacturer's site.
- The device is not allowed to be disposed of as household refuse. All locally valid regulations and requirements must be observed.
- When calculating the required torque, the specifications supplied by the damper manufacturer's (crosssection, design, installation site), and the air flow conditions must be observed.

Technical Drawing



Copyright by GRUNER AP @2025\_V1. Subject to change in technology and Design.